

# Food Grade KITO ELECTRIC CHAIN HOIST ER2

KITO's Food Grade ER2 Electric Chain hoists were carefully designed for lifting applications in food, beverage, and pharmaceutical processing industries where pristine cleanliness is critical. Food grade lubricants used on the load chain and in the gearbox are NSF H1 compliant for safe use in any facility where incidental contact with product is a concern.

## 125kg to 2t is now available

- Applicable for HACCP
- NSF H1 Compliant Food Grade Grease and Oil
- FEM class 3M/2M, JIS class M5/M4
- Grade 80, Nickel plated load chain
- Electromagnetic brake
- Robust Aluminum die-cast body
- IP55 Environmental Protection
- Selectable speed: single speed or Dual speed



# Food grade hoist CUSTOMIZED to FIT YOUR NEEDS!



Food grade  
Oil & grease



Stainless steel  
chain container



Plastic chain  
container



Pendant cover



Stainless steel  
hook



Stainless steel  
Bolt & nut



Epoxy paint

## Selection sample

CASE **A**



CASE **B**



CASE **C**



## Other options




Stainless steel rubber  
cushion & Nickel plated  
stopper on  
no-load side/load side



Stainless steel chain  
spring & limit plate



Canvas chain container



Stainless steel trolley  
wheels



Stainless steel guide  
roller



Nickel plated suspension shaft &  
susponder

## Headroom (mm) : minimum distance between hooks, or between rail bottom and hook

Capacity (Lifting speed)	Hook Suspended Type		Plain Trolley Type		Geared Trolley Type		Motorized Trolley Type	
	Standard hook	Stainless hook	Standard hook	Stainless hook	Standard hook	Stainless hook	Standard hook	Stainless hook
125kg (H)/250kg (S)	350	350	395	395	415	415	375	375
250kg (H)/500kg (L,S)	370	465	415	510	435	530	395	490
1t (L,S)	430	540	470	580	470	580	435	545
2t (L)	575	595	635	655	635	655	570	590
2t (S)	590	610	650	670	650	670	585	605

- The functions and performance of the products mentioned in the catalog have been designed based on the related regulations and standards. If they are used for other than their intended purposes such as being integrated into your equipment, we will not take any responsibility for accidents attributable to their unintended usages as well as guarantee their performance and functions. Never remodel our products.
- When you want to use our products for special purposes, consult us in advance.
- When you want to export our products, consult us in advance. There are different standards and regulations from one destination to another.
- It is prohibited to reprint, copy or divert all the information in this catalog (product patents, trademarks, photos, designs, copies, illustrations, etc.) without our consent.
- The specifications in this catalog are partly subject to change without prior notice.
- Product specifications may vary depending on the country. For more details please contact the nearest KITO dealer.

# KITO®

KITO CORPORATION

SHINJUKU NS Bldg, 9F, 2-4-1 Nishi-Shinjuku, Shinjuku-ku, Tokyo 163-0809 JAPAN

TEL: +81-3-5908-0180 FAX: +81-3-5908-0189

kito.co.jp KITO Global Website: kito.com

KITO CROSBY™